




Cleaver

SCIENTIFIC

quickspin



Occupying less than 6 inches square of bench space, the Quickspin has a very small footprint, making it easy to use in the lab. Rotors and adaptors, are supplied as standard to accommodate 1.5 ml, 0.5 ml and 0.4 ml tubes, as well as 0.2 ml strips and tubes. A highly durable stainless steel hinge pin facilitates easy opening of the translucent lid, while an on/off switch is located on the side of the centrifuge to start and stop operation. Alternatively, with the switch in the 'on' position, the centrifuge can be started and stopped by closing and opening the lid.

TECHNICAL SPECIFICATIONS

MAXIMUM SPEED	6000RPM
MAXIMUM G FORCE	2,000 x G
CAPACITY	8 x 1.5/2.0 ML 4 x 0.2 ML STRIPS
UNIT DIMENSIONS (W X L X H)	15 x 15 x 11.6 CM
WEIGHT	1.2 KG
TIME INCREMENTS / DECREMENTS	YES

The Quickspin is perfect for rapid spin-down of sample from the walls and caps of microcentrifuge tubes.

- SUPPLIED WITH BOTH STANDARD MICROTUBE AND STRIPTUBE ROTORS
- IDEAL FOR QUICK SPIN-DOWNS AND MICROFILTRATION
- STARTS AND STOPS IN SECONDS
- COMPACT DESIGN

ORDERING INFORMATION

Cat. No.	Description
CSLQSPINPLUS	Mini Centrifuge complete with 1.5/2.0 ml rotor, strip tube rotor, 0.5 and 0.4 ml adapters, 110V/230V

CLEAVER SCIENTIFIC LTD

Unit 41, Somers Road Industrial Estate,
Rugby, CV22 7DH
United Kingdom

T_ +44 (0)1788 565300
E_ INFO@CLEAVERSCIENTIFIC.COM
W_ WWW.CLEAVERSCIENTIFIC.COM