



MDF-DU303VXH-PE

TwinGuard eco

-86°C Upright Freezer

360 L



Next generation “Twin Guard” Dual Cooling system with reduced power consumption.

The next generation **Twin Guard Eco** Ultra Low Temperature freezer uses natural refrigerants, reducing energy usage up to 20%*, with enhanced access control via an electronic lock with facial recognition (optional) and NFC card protection (optional). To provide the highest level of security for your valuable samples.

Ultimate Sample Protection

The Dual Cooling System offers high levels of protection through the use of two independent refrigeration systems. If one system unexpectedly fails the other can maintain the freezer in the -75°C range.

Performance and Reliability

Naturally occurring hydrocarbon (HC) refrigerants have minimal effect on the environment. These refrigerants also provide more efficiency without compromising cooling performance, ambient tolerance, and recovery speeds following door openings.

Security control and Monitoring

An eye level, door mounted, 10.1 inches high resolution LCD touchscreen allows full user control. A USB port makes transferring logged data to a PC convenient. All performance attributes are displayed and an internal temperature log can be expressed in graphic form over time.




Valuable Sample Storage

Securely store valuable and irreplaceable samples with the upmost confidence that they won't be lost in the case of a compressor failure.



Natural Refrigerants

Natural refrigerants, compressors and integrated electronics are combined to lower operating costs resulting in less energy consumption and less heat output. Freezer operation is managed by effectively balancing temperature performance and energy management.



Electronic Door Lock

Know who entered the freezer and when. Track how long the door was open.

4 Ways to Lock

- Pin code
- Unique individual key
- Facial recognition (optional)
- Proximity Card (optional)

TwinGuard eco

-86°C Upright Freezer



Dual Cooling System

The Dual Cooling System offers ultimate sample protection. The two independent refrigeration systems provide a reliable and exceptionally stable -86°C ultra low temperature environment. If one system unexpectedly fails, the other can maintain the freezer in the -75°C range until service can be arranged.


Filterless Design

The filterless construction of the freezer reduces routine maintenance time by eliminating the need for regular cleaning of filters.

Innovative Cabinet Design

The enhanced cabinet design with chamfered edges reduces footprint for use in multi freezer laboratories.

Dimensions



Model Number		MDF-DU303VXH-PE	
External dimensions (W x D x H) ¹⁾	mm	670 x 882 x 1838	
Internal dimensions (W x D x H)	mm	490 x 600 x 1230	
Volume	litres	360	
Net weight	kg	225	
Capacity	2" boxes	288	
Performance			
Cooling performance ²⁾	°C	-86	
Temperature setting range	°C	-90 to -40	
Temperature control range ²⁾	°C	-86 to -40	
Control			
Controller		Microprocessor, non-volatile memory	
Display		LCD Touch Screen	
Temperature sensor		Pt-1000	
Refrigeration			
Refrigeration system		Independent Dual-Cooling	
Compressors	W	2 x 550	
Refrigerant		HC mixed refrigerant (R-600/R-170/R-50)	
Power Consumption at -80 °C, AT: 23 °C, unloaded		7.7 KWh/day	
Refrigerant weight in each cooling circuit	g	118	
GWP of refrigerant		GWP= 1.98	
Total Refrigerant weight (CO ₂ equivalent)	t	0.00024	
Insulation material		PUF / VIP Plus	
Insulation thickness	mm	80 mm	
Construction			
Exterior material		Painted Steel	
Interior material		Painted steel	
Outer doors	qty	1	
Outer door lock		Y	
Inner doors	qty	2	
Shelves	qty	3 [stainless steel]	
Max. load - per shelf	kg	50	
Vacuum release port	qty	1 automatic	
Access port	qty	3	
- position		back x 1, bottom x 2	
- diameter	Ø mm	17	
Casters	qty	4 (2 leveling feet)	
Alarms			
[R = Remote Alarm, V = Visual Alarm, B = Buzzer Alarm]			
Power failure		V-B-R	
High temperature		V-B-R	
Low temperature		V-B-R	
Filter		Filterless design	
Door open		V-B	
Electrical and noise level			
Power supply	V	220 / 230 / 240 V	
Frequency	Hz	50	
Noise level ³⁾	dB [A]	52	
Options			
Face recognition kit		MTR-FRC-PW	
NFC System ⁵⁾		NFC reader: MTR-NFC-PW	
	set of 5	IC Cards: MTR-IC-PW	
Liquid CO ₂ back-up		MDF-UB9-PW	
Temperature recorders	- Circular type	MTR-G85C-PE ⁴⁾	
	- Continuous strip type	Chart paper: RP-G85-PW / Ink pen: PG-R-PW	
		MTR-85H-PW ⁴⁾	
		Chart paper: RP-85-PW / Ink pen: DF-38FP-PW	
		Recorder housing: MDF-S3085-PW	
Recorder sensor cover		MTR-DU700SF-PW	
Mod-bus interface board		MTR-MODB1-PW	
Analog interface board		MTR-420MA-PW	

Appearance and specifications are subject to change without notice.

¹⁾Exterior dimensions of main cabinet only, excluding handle and other external projections

²⁾Air temperature measured at freezer centre, ambient temperature +30°C, no load

³⁾Nominal value - Background noise 20dB[A]

⁴⁾Requires sensor cover MTR-DU700SF-PW

⁵⁾The NFC System is only available in EEA member countries, UK, Switzerland, and Turkey.

PHC Europe

A Member of PHC Group

Eikdonk 1 | 4825 AZ Breda | Netherlands

T: +31 (0) 76 543 3833

www.phchd.com/eu/biomedical